



RIVA RACING
PERFORMANCE PRODUCTS & ACCESSORIES

Kawasaki Ultra Performance Ride Plate

RK21130



Applications:

2022+ Ultra 310 & 2023+ Ultra 160

Approximate Installation Time:

1 hour

Recommended Specialty Tools:

N/A

Required Materials:

Silicone Sealant 08909104

GET THE LATEST UPDATES!

Prior to installation, go to the RIVA Racing online Instruction Library to download the latest version of these instructions:

<https://rivaracing.com/instructions>

Your kit was inspected and verified before being carefully packaged by our staff. Please check package contents before beginning assembly. If you have a question about missing or damaged items please contact RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivaracing.com.

We strongly recommend the use of a service manual to familiarize yourself with the various components and procedures involved with this installation. Please note that some of the original hardware removed in the disassembly process will be used in the installation process. These instructions have been written in step-by-step format and refer to illustrations. Read through instructions entirely before performing installation. Please follow these step-by-step instructions and illustrations carefully.

***** ALLOW ENGINE TO COOL COMPLETELY BEFORE PERFORMING INSTALLATION *****


***** NO SMOKING *** NO SMOKING *** NO SMOKING *****

Caution: Whenever using electric or battery operated tools inside the hull be sure it is well ventilated and no fumes are present. Failure to do so could result in a fire, or explosion and serious personal injury or death.


This kit is not intended for use on pollution controlled vehicles. Installation on pollution controlled vehicles may constitute a violation of state or local statutes.

- INSTALLATION INSTRUCTIONS -

At the rear of your craft, locate the cable connected to the reverse gate (A) and disconnect.



Carefully cut silicone sealant (A) around edge of ride plate (C).



Remove bolts (B) securing OEM ride plate (C) to hull. Remove ride plate, with reverse gate.

Transfer reverse gate from OEM ride plate to RIVA Ride Plate. **NOTE: Apply blue Loctite to bolts. Torque bolts to 14 ft•lb (19 N•m).**

Thoroughly clean hull with a non-residual cleaner where ride plate was mounted, removing all excess silicone sealant.

Clean RIVA Ride Plate with a non-residual cleaner. Apply silicone sealant as indicated in illustration below.



Install ride plate and secure with bolts previously removed. **NOTE: Apply blue Loctite to bolts. Torque bolts to 69 in•lb (7.8 N•m).**

Connect reverse cable to reverse gate. Test reverse functionality for proper operation before riding your craft.

Allow silicone to cure for 24 hours before riding.

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact:

RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivaracing.com.

Limited Warranty

RIVA Ride Plates carry a 1-year limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice and a Return Authorization Number (RA#) must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.