




RIVA RACING
PERFORMANCE PRODUCTS & ACCESSORIES

GP1800 Power Filter Kit

RY13110



Applications: Yamaha GP1800 2017-

Approximate Installation Time: 1.0 hr.

Recommended Specialty Tools:

None

Part #

N/A

Required Materials:

Blue Loctite

Part #

Optional Accessories (not supplied in kit):

Water repellent Pre-Filter

Part #

RK13090PF-BK

We strongly recommend the use of a service manual to familiarize yourself with the various components and procedures involved with this installation. Please note that some of the original hardware removed in the disassembly process will be used in the installation process. These instructions have been written in step-by-step format and refer to illustrations. Read through instructions entirely before performing installation. Please follow these step-by-step instructions and illustrations carefully.

***** ALLOW ENGINE TO COOL COMPLETELY BEFORE PERFORMING INSTALLATION *****

***** NO SMOKING *** NO SMOKING *** NO SMOKING *****



RIVA RACING
PERFORMANCE PRODUCTS & ACCESSORIES

RY13110 GP1800 Power Filter Kit

COMPONENT LIST

	QUANTITY	PART NUMBER	DESCRIPTION
A	<input type="checkbox"/>	1	RK13090-2 Filter Element
B	<input type="checkbox"/>	1	Power Filter Tube
C	<input type="checkbox"/>	1	RY15-04/2.0 Silicone Coupler
D	<input type="checkbox"/>	3	203BL064-04 Hose Clamp
E	<input type="checkbox"/>	1	Bracket
F	<input type="checkbox"/>	1	Hose Adapter Assy.
G	<input type="checkbox"/>	1	7122A17 Hex Key
H	<input type="checkbox"/>	1	9753K54 Plastic Cap
I	<input type="checkbox"/>	1	Velocity Stack
J	<input type="checkbox"/>	1	Threaded Ring Assy
K	<input type="checkbox"/>	1	0096820 8 x 20 mm SS Hex Head Bolt
L	<input type="checkbox"/>	1	RY15-2NPF2 Lord Mount
M	<input type="checkbox"/>	1	410.8.24 8 mm Fender Washer
N	<input type="checkbox"/>	1	04478 8 mm Lock Washer
O	<input type="checkbox"/>	1	TY24MX Zip Tie

Packed with pride by: _____

Your kit was inspected and verified before being carefully packaged by our staff. Please check package contents before beginning assembly. If you have a question about missing or damaged items please contact RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivamotorsports.com

- INSTALLATION INSTRUCTIONS -

Disconnect lanyard. Remove seats.

Remove two screws holding plastic engine cover and pull cover up off rubber mounts. (Figure 1)

Figure 1




Disconnect engine breather hose from supercharger inlet hose. (Figure 2)

Figure 2



Loosen clamps (2) and remove hose between stock air box and supercharger and discard. (Figure 3)

Figure 3



Remove air filter case cover (8 clips, 2 on each side) with air filter and discard. (Figure 4)

Figure 4



Remove air filter case mounting bolts (4 total, 2 on each side) and then air filter case. Discard bolts and case.


(Figure 5)

Figure 5



Remove air filter case mounting bracket (4 nuts & washers) and discard. (Figure 6)

Figure 6



- INSTALLATION INSTRUCTIONS -

Remove the nut and washer inside the hull on the left seat bracket mounting stud. (Figure 7)

Figure 7



Install bracket inside hull on seat bracket stud. See figure 8 for proper orientation of bracket. Fasten with OEM nut and washer.


Figure 8



Thoroughly clean outside of supercharger inlet using a non-residual cleaner.

Install supplied billet threaded ring assy. onto supercharger inlet completely. Secure using supplied hex key wrench. (Figure 9) **NOTE: The side with the small shoulder must face the supercharger housing. DO NOT USE LOCTITE. Bolts come equipped with thread locking agent. Do not over tighten bolts.**

Figure 9



Carefully screw (right-handed threads) supplied velocity stack onto billet adapter flange. **NOTE: Do not over tighten. Velocity stack only needs to be snug.** (Figure 10)

Figure 10




Install supplied lord mount into threaded brass insert in Power Filter tube. **NOTE: Apply blue Loctite to stud. Do not over tighten**

Install supplied Power Filter onto end of tube with threaded brass insert and secure. **Tip: lubricate inside of filter and outside of tube with glass cleaner. NOTE: Do not over tighten clamp.**

Install supplied silicone coupler onto opposite end of Power Filter tube. Secure using one supplied hose clamp. **Tip: lubricate inside of coupler and outside of tube with glass cleaner. NOTE: Do not over tighten clamp.** (Figure 11)

Figure 11



Place second supplied clamp over adapters on supercharger inlet.

At front of engine insert Power Filter tube assembly into engine compartment over fuel tank (Power Filter end first).

Lower coupler end of Power Filter tube assembly into place by rotating towards supercharger. Place coupler at an angle over left side of velocity stack on supercharger inlet.


Install by rotating Power Filter tube assembly while pulling

- INSTALLATION INSTRUCTIONS -

towards engine. (Figure 12) **Tip: lubricate inside of coupler, inside of tube, and outside of velocity stack with glass cleaner. NOTE: Velocity stack fits into Power Filter tube.**

Ensure Power Filter tube is installed onto velocity stack completely.

Figure 12



Locate lord mount on Power Filter tube. Rotate Power Filter tube towards mounting bracket until aligned. Secure lord mount to bracket using supplied M8 bolt, M8 lock washer and M8 fender washer. **NOTE: Apply blue Loctite to bolt. Do not over tighten bolt.** Tighten clamp for coupler at supercharger inlet. **NOTE: Do not over tighten clamp.**

Using supplied adapter hose and OEM clip install engine breather hose onto fitting at center of Power Filter tube. Secure with supplied zip tie. (Figure 13) If using RIVA Catch Can Breather install supplied plastic cap on Power Filter tube fitting using supplied zip tie.

Figure 13



Replace plastic engine cover. **NOTE: Apply blue Loctite to bolts. Do not over tighten bolts.**

Check bilge for tools, rags, etc. Run craft on a flush kit to check for proper operation.

Remember, the water belongs to everyone.

Please ride responsibly and respect the environment!

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact:

RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivamotorsports.com.

Limited Warranty

RIVA Power Filter Kits carry a 1 year limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice and a Return Authorization Number (RA#) must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.

This area intentionally left blank