



P/N# RY2718

RIVA GP Trim Tab Kit

Applications: '97 & early '98 GP760/800/1200

<i>Parts List:</i>	<i>Qty.</i>	<i>Description</i>
	2	RIVA Trim Tab Backing Plates
	1	RIVA Trim Tab Left Side
	1	RIVA Trim Tab Right Side
	8	Mounting Screws

Note: This is a racing component. It is designed for competition only. The Yamaha limited warranty or Riva Yamaha does not cover failures caused by this component

WARNING! DISCONNECT BATTERY AND TURN FUEL OFF BEFORE PERFORMING WORK.

1. Disconnect negative and positive leads from battery. Turn fuel off.
2. Remove left and right OEM trim tabs, by removing waterbox, waterbox strap, battery box, exhaust through-hull outlet and hull foam to gain access to eight 10mm nuts holding (four nuts on each trim tab) OEM trim tabs in place.
3. Clean hull trim tab mounting area inside and outside.
NOTE: It may be necessary to trim epoxy inside hull by ride plate inserts for proper mounting of RIVA trim tab backing plate.
4. Using structural adhesive* install left and right RIVA Trim Tab backing plates to inside of hull by positing in place over existing trim tab screw holes. Position each Riva Trim Tab on outside of hull with countersunk holes facing down, long beveled edges facing forward and insert each supplied screw through the RIVA Trim Tab, hull, and into the threaded holes in left and right mounted backing plate inside hull.
NOTE: Use silicone on surface of RIVA Trim Tab to prevent any water leaks and apply Loctite 242 to all supplied screws.
5. Reinstall removed foam, exhaust through-hull outlet, battery box, waterbox strap, and water box.
6. Reattach positive and negative leads to battery and check for any hull leaks.

* Structural Adhesives recommend are; 3M Structural Adhesive Tube kit. 3M 5200 Adhesive Sealant, or Plio-grip 7770 (all available at RIVA Racing).

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact:
RIVA Technical Support directly at (954) 247-0705 or by e-mail at
tech_support@rivamotorsports.com

RIVA Trim Tab Kit Limited Warranty

RIVA Racing warrants this RIVA Trim Tab Kit to the original purchaser to be free of defects in materials and workmanship under normal use and service for a period of 90 days from the date of original purchase by the end user.

RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA freight prepaid within the warranty period. Any equipment returned which RIVA's opinion has been subjected to misuse, abuse, corrosion or accident shall not be covered by this warranty. *Hardware, stripped threads, and broken fasteners are not covered by warranty.*

RIVA Racing shall have no liability for special, incidental, or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental, or consequential damages and, therefore, the above exclusion or limitation may not apply to you.

Warranty does not include expenses related to freight or transportation of parts, or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.