



WORX RACING SPONSONS KIT

PART # - WR531

MODELS: HONDA F-12/F-12X/F-12X GPSCAPE

INSTALLATION INSTRUCTIONS

| | |
|-----------------|--|
| Parts Supplied: | 2 x WORX Racing adjustable sponson paddles 2 x WORX Racing Backing rails 8 x M6 x 30 Hex head bolts 8 x $\frac{1}{4}$ x $\frac{5}{8}$ Flat washers 8 x $\frac{1}{4}$ x 1 $\frac{1}{4}$ Button head bolts 8 x $\frac{1}{4}$ x $\frac{3}{4}$ Flat Washers |
|-----------------|--|

IMPORTANT: READ ALL INSTRUCTIONS BEFORE PROCEEDING WITH INSTALLATION

- 1- Make sure ski is secure and on a flat surface. Remove lanyard.
- 2- Remove OEM Sponson paddles from hull. Clear all excess silicone from behind the OEM sponsons.
- 3- Run a bead of Marine silicone sealant around 4 mounting holes on hull and a bead along both sides of the Sponson Backing rail. Fit backing rail to hull using M6 x 30 bolts and $\frac{1}{4}$ x $\frac{5}{8}$ Flat washers.
- 4- Fit the sponsons paddles using the remaining ($\frac{1}{4}$ x 1) bolts with the ($\frac{1}{4}$ x $\frac{3}{4}$) flat washers supplied (start all of the bolts into the side rail before tightening).
- 5- Adjust the sponsons to your riding style: Most people prefer the fully down position for the most aggressive performance.
- 6- After riding for about 15 minutes check that your sponson bolts are tight and when you have decided which position best suits your riding style it is recommended that you apply a layer of marine silicone sealant between the side rails and the sponsons and also apply loctite to the mounting bolts.
- 7- **Regularly check that the sponson fixing bolts are tight.** **Warning:** These sponsons will vastly improve the turning capability of your boat. Take time to get used to them before you attempt any hard cornering

Thank you for purchasing **Worx Racing components** products. We firmly believe that **Worx Racing Components** products are among the finest watercraft parts available. A great deal of time and effort has gone into the design and development of this product to ensure that it will perform to the highest standard and that installation is a relatively straight forward and simple procedure. If you have any questions or comments on the performance and/or installation of our products please contact us at the numbers listed on page one or through your local **Worx** dealer.